

TECHNICAL DATASHEET

Reflective Badges Domestic Wash



Reflective Badges



Domestic Wash

TECHNICAL DATASHEET

www.ja-int.com

APPLICATION

Temperature (°C): 160-180°C
Temperature (°F): 320-356°F
Time: 10-12 seconds

Pressure: Medium to 42.7 - 56.9 psi / 2.9 - 3.9 bar / 3.0 - 4.0 kg/cm2

Low 28.4 - 42.7 psi / 2.0 - 2.9 bar / 2.0 - 3.0 kg/cm2

Carrier Release: Before Application

LAUNDERING

Suitable for domestic wash up to 40°C Tumble Dry - Medium Iron - Medium, On Reverse Do Not Dry-Clean Do Not Bleach

HANDLING AND STORAGE

Store in a cool, dry environment Keep away from direct sunlight

Do not attempt to apply any transfer that has been removed from its carrier Direct contact with sweat or oils can cause stains/blemishes in the reflective surface. We recommend that gloves be worn when applying in order to preserve the finish of the product.

COMPOSITION

Micro glass-bead reflective film Print - Solvent-based Inks Adhesive - PES Carrier - Polyester

HEALTH & SAFETY

This product is identified as Non-Hazardous to the end user No PPE is required during application**

ENVIRONMENTAL / RECYCLING

Vinyl - non-recyclable Polyester carrier - non-recylable Vegan-Friendly: No

CERTIFICATION

Reflective/wash Standards - EN 471:2003 Class 2 & ANSI/ISEA 107-1999 Level 2 (Base Material Only) EN ISO 20471:2013

V1.0

^{*}Printed ink blocks reflectivity of base material

^{**}Any furnes created by this transfer during application are harmless. However, modern garment materials can be coated and finished in many different ways; some of which may alter their application and health & safety requirements. We recommend thorough checking and testing of any garment material to determine the correct requirements before application.